



	SYMBOL	MIN	NOM	MAX	
TOTAL THICKNESS	A	0.75	0.8	0.85	
STAND OFF	A1	0.02	0.05	0.08	
MOLD THICKNESS	A2	0.675 REF			
L/F THICKNESS	A3	0.13 REF			
LEAD WIDTH	b	0.2	0.25	0.3	
	b1	0.575	0.625	0.675	
	b2	0.1 REF			
BODY SIZE	X	D	11 BSC		
	Y	E	11 BSC		
LEAD PITCH	e	0.7 BSC			
EP SIZE	X	J	4.2	4.3	4.4
	Y	K	4.2	4.3	4.4
LEAD LENGTH	L	0.575	0.625	0.675	
	L1	0.1 REF			
PACKAGE EDGE TOLERANCE	aaa	0.1			
MOLD FLATNESS	bbb	0.2			
COPLANARITY	ccc	0.1			
LEAD OFFSET	ddd	0.08			
EXPOSED PAD TOLERANCE	eee	0.1			

**NOTES**

1.0 COPLANARITY APPLIES TO LEADS, CORNER LEADS AND DIE ATTACH PAD.

<b>ASE Group</b>		PROJ.		
<b>TITLE:</b>	PACKAGE OUTLINE	<b>DWG. NO.</b>	98A0151AN001	
	151 LD AQFN EXPOSED PAD		<b>REV.</b>	A
	11 X 11 X 0.85 MM 0.7 PITCH (FOR INOVA ONLY)	<b>SHEET</b>	1 OF 2	<b>SIZE</b>
<b>UNIT</b>	<b>DIMENSION AND TOLERANCES</b>	<b>REFERENCE DOCUMENT</b>		
MM	ASME Y14.5M	---		

